



TECHNICAL PAINT SERVICES

A130 ANTI-CLIMB SECURITY PAINT

Features:

A non-drying paint which gives a slippery surface to deter intruders and vandals. For additional protection, a special dye can be added which will stain the clothing and skin of an intruder if an attempt to remove the paint with solvent is made, and which is exceptionally difficult to remove. Suitable for direct application to concrete posts, gutters, asbestos and metal roofs, down pipes, fences and walls.

Availability:

Black, Grey, Green and Red in 5 Litre containers.

Volume Solids:

77% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from dirt and loose material. A130 may be applied to any existing painted surface. For new, untreated surfaces the following priming systems are recommended:

Iron and Mild Steel:	AP79 Universal Primer.
Galvanised Steel:	X85 Mordant Solution, followed by AP86 Calcium Plumbate Primer.
Aluminium:	UP89 or UP90 Two Pack Etching Primer.
Asbestos:	R10/70/1 Chlorinated Rubber Clear Sealer.
Wood:	AP91 Non Lead Wood Primer.
Concrete:	ES27/70/4 Emulsion Acrylic Clear.

Application:

Brush, roller or trowel. Supplied ready for use. Use X156 White Spirit for cleaning. Apply one thick coat for best results. If applying dyed version, wear plastic disposable gloves.

Coverage:

Approximately 15 - 20 sq metres per 5 Litres per coat, depending on substrate and method of application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.