



TECHNICAL PAINT SERVICES

A30 FLOOR FINISH ALKYD

Features:

A high quality, moderately priced lead free synthetic floor finish suitable for interior or exterior use. Resistant to water, common engineering oil, petrol and light chemicals. Ideal for use on weathered concrete, wood, metal and timber floors, and can be applied over most existing paints without lifting. This paint should not be applied over PVA sealer, latex self leveling compound or power floated concrete. Please contact our Technical Department. A30 Contract Grade available, minimum 5 Litres.

Availability:

All BS4800 colours plus Clear in 5, 2.5 and 1 Litre containers.
A31 Floor Finish Alkyd Non-Slip is also available.

Volume Solids:

55% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease. Concrete floors must be at least 6 months old before application of A30. For newer concrete, please contact our Technical Department.

Application:

By brush, roller or spray. Supplied ready for use for brushing. Thin up to 25% by volume, with UTR112 Universal Synthetic Thinners, for roller or spray application. Do not use when air temperature is below 5°C, or during high humidity.

Coverage:

40 sq metres per 5 Litres per coat @ 25 microns dry film thickness.

Drying:

Touch dry: 6 - 8 hours @ 20°C.

Recoat after overnight drying.

Light foot traffic after 24 hours.

Full use: 2 - 3 days.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.