



TECHNICAL PAINT SERVICES

AP56/70 DEEP BINDING CLEAR

Features:

An oil based sealer providing deep penetration of porous surfaces forming a hard, water-repellent seal on cement rendering, asbestos, brickwork, concrete, block work, roughcast, pebble dash and substrates previously finished with distemper and emulsion paint, prior to application of oil based or emulsion paints.

Availability:

In 5, 2.5 and 1 Litre containers.

Volume Solids:

22% ± 3% (BS 3900 Part A10).

Preparation:

The substrate should be thoroughly clean, dry and free from dust and grease. Remove any loose or flaking material before sealing.

Application:

Brush or roller. A first coat should be applied, thinned up to 10% by volume with X156 White Spirit and allowed to dry. A second coat should then be applied.

Coverage:

Approximately 60 sq metres per 5 Litres depending on porosity of substrate.

Drying:

Touch dry: 4 hours @ 20°C.

Hard dry & recoatable: 8 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.
See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.